



Loudspeaker cables - (N)YFAZ

Technical attributes

Construction	single wires
Outer sheath	PVC
Temperature range min., mobile operation	-15 °C
Temperature range max., mobile operation	+70 °C
Nominal voltage U ₀ /U	300/300 V

Description

Used primarily as a speaker cable for hifi applications

Product table

product number	product name	Weight ca. [kg]	Cu-weight [kg]	Outer-Ø ca. [mm]	Outer sheath colour
02502001	(N)YFAZ 2 x 0,5 bk	15,00	9,60	4,10	black
02502002	(N)YFAZ 2 x 0,5 wh	15,00	9,60	4,10	white
02502003	(N)YFAZ 2 x 0,5 bn	15,00	9,60	4,10	brown
02502023	(N)YFAZ 2 x 0,5 gy	15,00	9,60	4,10	grey
02502005	(N)YFAZ 2 x 0,75 bk	20,00	14,40	4,50	black
02502006	(N)YFAZ 2 x 0,75 wh	20,00	14,40	4,50	white
02502007	(N)YFAZ 2 x 0,75 bn	20,00	14,40	4,50	brown
02502008	(N)YFAZ 2 x 0,75 rd/bk	20,00	14,40	4,50	red/black
02502021	(N)YFAZ 2 x 0,75 gy	20,00	14,40	4,50	grey
02502022	(N)YFAZ 2 x 1 wh	25,00	19,50	5,00	white
02502028	(N)YFAZ 2 x 1 bk	25,00	19,50	5,00	black
02502031	(N)YFAZ 2 x 1 rd/bk	25,00	19,50	5,00	red/black
02502009	(N)YFAZ 2 x 1,5 bk	37,00	28,80	5,50	black
02502010	(N)YFAZ 2 x 1,5 wh	37,00	28,80	5,50	white
02502011	(N)YFAZ 2 x 1,5 bn	37,00	28,80	5,50	brown
02502012	(N)YFAZ 2 x 1,5 rd/sw	37,00	28,80	5,50	red/black
02502024	(N)YFAZ 2 x 1,5 gy	37,00	28,80	5,50	grey
02502013	(N)YFAZ 2 x 2,5 bk	66,00	48,00	6,70	black
02502014	(N)YFAZ 2 x 2,5 wh	66,00	48,00	6,70	white
02502016	(N)YFAZ 2 x 2,5 rd/bk	66,00	48,00	6,70	red/black
02502029	(N)YFAZ 2 x 2,5 gy	66,00	48,00	6,70	grey/black
02502017	(N)YFAZ 2 x 4 bk	80,00	76,80	8,80	black



Loudspeaker cables - (N)YFAZ

product number	product name	Weight ca. [kg]	Cu-weight [kg]	Outer-Ø ca. [mm]	Outer sheath colour
02502018	(N)YFAZ 2 x 4 wh	80,00	76,80	8,80	white
02502019	(N)YFAZ 2 x 4 bn	80,00	76,80	8,80	brown
02502020	(N)YFAZ 2 x 4 rd/bk	80,00	76,80	8,80	red/black
02502030	(N)YFAZ 2 x 4 gn	80,00	76,80	8,80	grey

